

M80
(Ball)



M62
(Tracer)



M61
(Armor piercing)



API
(Armored piercing incendiary)



APT
(Armored piercing tracer)



M118
(Sniper)



CHARACTERISTICS

Projectile weight	9,67 g	9,46 g	9,75 g	8,75 g	9,75 g	10,9 g
Projectile length	29,46 mm	34,29 mm	32,2 mm	32,2 mm	32,2 mm	31,9 mm
Propellant charge	~2,85 g	~2,8 g	~2,82 g	~2,82 g	~2,82 g	~2,7 g
Muzzle velocity	828 ± 9,1 m/s	817 ± 9,1 m/s	838 ± 9,1 m/s	838 ± 9,1 m/s	917 ± 9,1 m/s	777 ± 9,14 m/s
Accuracy Rs	max A:12,7 B:19,1 cm at 549 m	max 38,1 cm at 549 m	max 19,1 cm at 549 m	max 19,1 cm at 549 m	max 38,1 cm at 549 m	max 8,89 cm at 548 m
Tracer burning time		90 to min 777 m			92 to min 777 m	

- **Penetration (AP M61; API, APT):** The bullet of the sample cartridges shall demonstrate complete penetration of 6 mm thick nickel-chromium steel plate target located 100 meters from the weapon..
- **Incendiary (API):** At 100 m, the incendiary composition of bullets shall ignite paper soaked in petrol located behind the armorplate.
- **Accuracy :** A* : for ammunition scheduled for packaging in cartons or clip
B* : for ammunition scheduled for packaging in links.

PACKING

PACKAGE 1

- 20 rounds in cardboard box
- 10 cardboard boxes (200 rounds) in PVC bag
- 5 PVC bags in wooden case

PACKAGE 2

- 250 rounds in metal link belt M13 (4Ball:1 Tracer)
- 1 metal link belt in metal box M19A1
- 4 metal boxes (1000 rounds) in wire bound wooden box

PACKAGE 3

- 250 rounds in metal link belt M13
- 2 metal link belts in metal box M2A1
- 2 metal boxes M2A1 (1000 rounds) in wire bound wooden box

PACKAGE 4

- 20 rounds in cardboard box
- 28 cardboard boxes (560 rounds) in metal box M2A1
- 2 metal boxes (1120 rounds) in wire bound wooden box